

# docker-compose.yml

```
version: "3.8"

services:
  immich-server:
    image: altran1502/immich-server:release
    entrypoint: ["/bin/sh", "./start-server.sh"]
    volumes:
      - ${UPLOAD_LOCATION}:/usr/src/app/upload
    env_file:
      - .env
    environment:
      - NODE_ENV=production
    depends_on:
      - redis
      - database
    restart: always

  immich-microservices:
    image: altran1502/immich-server:release
    entrypoint: ["/bin/sh", "./start-microservices.sh"]
    volumes:
      - ${UPLOAD_LOCATION}:/usr/src/app/upload
    env_file:
      - .env
    environment:
      - NODE_ENV=production
    depends_on:
      - redis
      - database
    restart: always

  immich-machine-learning:
    image: altran1502/immich-machine-learning:release
    entrypoint: ["/bin/sh", "./entrypoint.sh"]
    volumes:
      - ${UPLOAD_LOCATION}:/usr/src/app/upload
```

```
env_file:
  - .env
environment:
  - NODE_ENV=production
depends_on:
  - database
restart: always
```

```
immich-web:
  image: altran1502/immich-web:release
  entrypoint: ["/bin/sh", "./entrypoint.sh"]
  env_file:
    - .env
  restart: always
```

```
redis:
  container_name: immich_redis
  image: redis:6.2
  restart: always
```

```
database:
  container_name: immich_postgres
  image: postgres:14
  env_file:
    - .env
  environment:
    POSTGRES_PASSWORD: ${DB_PASSWORD}
    POSTGRES_USER: ${DB_USERNAME}
    POSTGRES_DB: ${DB_DATABASE_NAME}
    PG_DATA: /var/lib/postgresql/data
  volumes:
    - pgdata:/var/lib/postgresql/data
  restart: always
```

```
immich-proxy:
  container_name: immich_proxy
  image: altran1502/immich-proxy:release
  ports:
    - 2283:80
  logging:
    driver: none
```

```
depends_on:
```

```
  - immich-server
```

```
restart: always
```

```
volumes:
```

```
  pgdata:
```

---

Revision #3

Created 17 August 2022 19:43:03 by DB T3CH

Updated 18 August 2022 14:08:58 by DB T3CH