

Docker-Compose

```
version: '3'

services:
  db:
    image: postgres:15
    volumes:
      - joplindb:/var/lib/postgresql/data
    ports:
      - "5432:5432"
    restart: unless-stopped
    environment:
      - POSTGRES_PASSWORD=POSTGRES_PASSWORD
      - POSTGRES_USER=POSTGRES_USER
      - POSTGRES_DB=POSTGRES_DATABASE

  app:
    image: joplin/server:latest
    depends_on:
      - db
    ports:
      - "22300:22300"
    restart: unless-stopped
    environment:
      - APP_PORT=22300
      - APP_BASE_URL=https://yourwebsite.com
      - DB_CLIENT=pg
      - POSTGRES_PASSWORD=POSTGRES_PASSWORD
      - POSTGRES_DATABASE=POSTGRES_DATABASE
      - POSTGRES_USER=POSTGRES_USER
      - POSTGRES_PORT=5432
      - POSTGRES_HOST=db
      - MAILER_ENABLED=1
      - MAILER_HOST=smtp.gmail.com
      - MAILER_PORT=465
      - MAILER_SECURE=1
      - MAILER_AUTH_USER=you@yourdomain.com
      - MAILER_AUTH_PASSWORD=3m@1lPa55w0rD
```

- MAILER_NOREPLY_NAME=JoplinServer
- MAILER_NOREPLY_EMAIL=you@yourdomain.com

volumes:

joplindb:

Revision #3

Created 15 February 2023 13:51:15 by DB T3CH

Updated 15 February 2023 22:50:54 by DB T3CH