

x86 Docker-Compose.yml

```
version: '2'

volumes:
  nextcloud:
  db:

services:
  db:
    image: mariadb
    restart: always
    command: --transaction-isolation=READ-COMMITTED --binlog-format=ROW --innodb-file-per-table=1 --skip-innodb-read-only-compressed

    volumes:
      - db:/var/lib/mysql
    environment:
      - MYSQL_ROOT_PASSWORD=Bund7zXeVz7YnFknLGcnUjHtk #change this
      - MYSQL_PASSWORD=HFdMe9rn5kf7A8Pqc8v86Pre5 #change this
      - MYSQL_DATABASE=nextcloud
      - MYSQL_USER=nextcloud

  app:
    image: nextcloud
    restart: always
    ports:
      - 8888:80
    links:
      - db
    volumes:
      - nextcloud:/var/www/html
    environment:
      - MYSQL_PASSWORD=HFdMe9rn5kf7A8Pqc8v86Pre5 #change this to match the mysql_password
above
      - MYSQL_DATABASE=nextcloud
      - MYSQL_USER=nextcloud
```

- MYSQL_HOST=db

The command in the db service has been modified from the original to prevent the following error:

4047 InnoDB refuses to write tables with ROW_FORMAT=COMPRESSED or KEY_BLOCK_SIZE.

This solution was found [here](#).

Revision #4

Created 23 September 2021 16:38:13 by DB T3CH

Updated 1 November 2021 15:25:48 by DB T3CH