

Docker-Compose.yml

```
version: '3'

services:
  db:
    image: mariadb:10
    command: --character-set-server=utf8mb4 --collation-server=utf8mb4_unicode_ci
    environment:
      MYSQL_ROOT_PASSWORD: supersecret
      MYSQL_USER: vikunja
      MYSQL_PASSWORD: secret
      MYSQL_DATABASE: vikunja
    volumes:
      - ./db:/var/lib/mysql
    restart: unless-stopped
  api:
    image: vikunja/api
    environment:
      VIKUNJA_DATABASE_HOST: db
      VIKUNJA_DATABASE_PASSWORD: secret
      VIKUNJA_DATABASE_TYPE: mysql
      VIKUNJA_DATABASE_USER: vikunja
      VIKUNJA_DATABASE_DATABASE: vikunja
      VIKUNJA_SERVICE_FRONTENDURL: https://your-frontend-url.com/
      VIKUNJA_SERVICE_ENABLETASKATTACHMENTS: 1
      VIKUNJA_SERVICE_ENABLEREGISTRATION: 1
      VIKUNJA_SERVICE_ENABLEEMAILREMINDERS: 1
      VIKUNJA_MAILER_ENABLED: 1
      VIKUNJA_MAILER_FORCESSL: 1
      VIKUNJA_MAILER_HOST: smtp.gmail.com
      VIKUNJA_MAILER_PORT: 465
      VIKUNJA_MAILER_USERNAME: youremail@gmail.com
      VIKUNJA_MAILER_PASSWORD: Y0uRp@55W0rD!
    volumes:
      - ./files:/app/vikunja/files
    depends_on:
      - db
```

```
    restart: unless-stopped
frontend:
  image: vikunja/frontend
  restart: unless-stopped
proxy:
  image: nginx
  ports:
    - 8022:80
  volumes:
    - ./nginx.conf:/etc/nginx/conf.d/default.conf:ro
  depends_on:
    - api
    - frontend
  restart: unless-stopped
```

Revision #1

Created 23 September 2021 16:19:37 by DB T3CH

Updated 23 September 2021 16:20:06 by DB T3CH